



## **Declaration of Performance**

DoP Reference:		CPR 2013 Euroform-Eas	syboard.001 07-04-2023
Replaces:	Not Applicable		
Unique identification code of the product-type	Easyboard®		
Type, batch or serial number or other element allowing	-		
identification of the construction product – Article 11(4)  3. Intended use or uses of the construction product as	See product label and associated documents		
foreseen by the manufacturer	Fibre cement flat sheet for use as non-structural components		
Name, registered trade name or trade mark and contact address of the Manufacturer – Article 11(5)	Euroform Products Ltd, Unit 2, Lyncastle Road, Appleton, Warrington, Cheshire WA4 4SN		
5. Name and address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	MIT International Trade S.L., Ctra. Sarria a Vallvidrera, 259 local 08017, Barcelona, Spain T: + 34 93 406 98 85		
6. System of assessment and verification of constancy of	3 – Fire Test		
the construction products as set out in Annex V	4 – all other parameters		
	Efectis No. 1812		
7. Name and identification number of the Notified Body	performed Reaction to Fire Classification		
concerning a construction product covered by a harmonised standard			
	to system		N 13501-1 2018
	Issued Report RC EFR-23-001681A		
	Not relevant		
Name and identification number of the Technical     Assessment Body concerning a construction product     covered by a Technical Assessment	ETA ref. Not relevant		
	basis		
	performed		
	to system		Not relevant
	issuea	Issued Not relevant	
Declared performance according to:			)12+A2:2018
Essential Characteristic		Performance	Harmonised technical specification
Dimensional Tolerance			
- Length		L1	
- Width		L1	EN 12467:2012+A2:2018
- Thickness		L1	LN 12407.2012 A2.2018
- Squareness		L2	
Type of Board		NT	EN 12467:2012+A2:2018
Mechanical Resistance		Class B1	EN 12467:2012+A2:2018
- Release of dangerous substance		NPD	Not Applicable
- Reaction to Fire		A1	EN 13501-1:2018
Water Impermeability	-	Pass	EN 12467:2012+A2:2018
		rass	EN 12407.2012+A2.2018
Durability against			
- warm water			
- soak / dry		Category B	EN 12467:2012+A2:2018
- Freeze-Thaw			
- heat-rain			
Density		>1,000 kg/m³	EN 12467:2012+A2:2018
205.07		/g/	
	<del>                                     </del>		
	<del>                                     </del>		
	1		
	1		
	<del> </del>		
	<b></b>		
	<u> </u>		
	<del>                                     </del>		
	<del> </del>		
All other essential characteristics not identified above		NPD	NPD = No Performance Declared
			e-signature for Management Systems e-signature for management systems
<ul><li>10. The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance issued under the sole</li></ul>			e-signature for management systems e-signature for Management Systems
2 is in conformity with the declared performance in point 9. This declaration of performance issued under the sole	Signed on l	behalf of the manufacturer	e-signature for Management Systems e-signature for management systems e-signature for management systems se-signature for Management Systems e-signature for management Systems
2 is in conformity with the declared performance in point			e-signature for Management Systems seculature for Mana
2 is in conformity with the declared performance in point 9. This declaration of performance issued under the sole	Name 8	behalf of the manufacturer & function of signatory Ite & place of issue	e-signature for Management Systems e-signature for