


Declaration of Performance

DoP Reference:	CPR 2013 Euroform-Versaroc MPA1.002 01-12-2022	
Replaces:	CPR 2013 Euroform-Versaroc MPA1.001 04-12-2019	
1. Unique identification code of the product-type	Versaroc® MPA1	
2. Type, batch or serial number or other element allowing identification of the construction product – Article 11(4)	See product label and associated documents	
3. Intended use or uses of the construction product as foreseen by the manufacturer	Fibre cement flat sheet for internal and external use as non-structural components.	
4. Name, registered trade name or trade mark and contact address of the Manufacturer – Article 11(5)	Euroform Products Ltd, Unit 2, Lyncastle Road, Appleton, Warrington, Cheshire WA4 4SN	
5. Name and address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	MIT International Trade S.L., Ctra. Sarria a Vallvidrera, 259 local 08017, Barcelona, Spain T: + 34 93 406 98 85	
6. System of assessment and verification of constancy of the construction products as set out in Annex V	3 – Fire Test 4 – all other parameters	
7. Name and identification number of the Notified Body concerning a construction product covered by a harmonised standard	Ensatec N.B. 1668	
	performed	Reaction to Fire Classification
	to system	EN 13501-1:2018
	Issued	Report
	Not relevant	
8. Name and identification number of the Technical Assessment Body concerning a construction product covered by a Technical Assessment	ETA ref.	Not relevant
	basis	Not relevant
	performed	Not relevant
	to system	Not relevant
	Issued	Not relevant
9. Declared performance according to:	EN 12467:2012+A2:2018	
Essential Characteristic	Performance	Harmonised technical specification
Type of sheet	NT	EN 12467:2012+A2:2018
Mechanical Resistance	Category A, Class 2	EN 12467:2012+A2:2018
Dimensional Tolerances		
- Length	L1	EN 12467:2012+A2:2018
- Width	L1	
- Thickness	L1	
- Squareness	L1	
- Straightness of edge	L2	
Reaction to Fire	A1	EN 13501-1:2018
Release of Dangerous Substances	NPD	EN 12467:2012+A2:2018
Water Impermeability	No water drops	EN 12467:2012+A2:2018
Durability against		
- Warm Water	R _L ≥ 0.75	EN 12467:2012+A2:2018
- Soak / Dry	R _L ≥ 0.75	
- Freeze / Thaw	R _L ≥ 0.75	
- Heat / Rain	Pass	
All other essential characteristics not identified above	NPD	NPD = No Performance Declared

10. The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance issued under the sole responsibility of the manufacturer identified in point 4.	Signed on behalf of the manufacturer	
	Name & function of signatory	Spencer Robinson – Managing Director
	Date & place of issue	01/12/2022 - Warrington